



# EC declaration of conformity

For the following equipment:

Product Name: Switching Power Supplies

Model Designation: LRS-150x-y (x= F; y=5,12,15,24,36,48) (x=Blank; y=12,15,24,36,48)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied:

# RoHS Directive (2011/65/EU) Low Voltage Directive (2006/95/EC):

EN61558-1:2005+A1:2009/EN61558-2-16:2009+A1

EN60950-1:2006+A11+A1+A12+A2 EN60335-1:2012+A11/EN62233:2008 TUV certificate No: R50311825 TUV certificate No: R50315938 TUV certificate No: R50313573

Class B

Class B

## Electromagnetic Compatibility Directive (2004/108/EC):

# **EMI (Electro-Magnetic Interference)**

Conducted emission / Radiated emission

EN55022:2010 EN55011:2009+A1:2010 (Group 1) EN61000-6-3:2007+A1:2011

EN55014-1:2006+A1:2009+A2:2011

Harmonic current EN61000-3-2:2014

Voltage flicker EN61000-3-3: 2013

## **EMS (Electro-Magnetic Susceptibility)**

| EN55024:2010 EN61000-6-2:2005 EN61204-3:2000 EN55014-2:1997+A1:2001+A2:2008 |  |                |                                     |
|---|--|----------------|-------------------------------------|
| ESD air   | EN61000-4-2:2009                       | Level 3        | 8KV                                 |
| ESD contact   | EN61000-4-2:2009                       | Level 2        | 4KV                                 |
| RF field susceptibility   | EN61000-4-3:2006+A1:2008+A2:2010       | Level 3        | 10V/m                               |
| EFT bursts  | EN61000-4-4:2012                       | Level 3        | 2KV/5KHz                            |
| Surge susceptibility  | EN61000-4-5:2006                       | Level 3        | 2KV/Line-Line                       |
| Surge susceptibility  | EN61000-4-5:2006                       | Level 4        | 4KV/Line-Earth                      |
| Conducted susceptibility  | EN61000-4-6:2014                       | Level 3        | 10V                                 |
| Magnetic field immunity   | EN61000-4-8:2010                       | Level 4        | 30A/m                               |
| Voltage dip, interruption   | EN61000-4-11:2004 >95% dip 0.5 periods | 30% dip 25 per | iods >95% interruptions 250 periods |

#### Note

A component power supply with load will be installed into final equipment which consists of an electronically shielded metal enclosure. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.

The EMC tests mentioned above are performed using a well defined metal plate to simulate said metal enclosure.

For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies".(as available on <a href="http://www.meanwell.com">http://www.meanwell.com</a>)" and TDF (Technical Documentation File).

This Declaration is effective from serial number EB5xxxxxxx

Person responsible for marking this declaration:

Mean Well Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 248, Taiwan

(Manufacturer Address)

Johnny Huang/Senior Verification Engineer:

(Name / Position)

(Signature)

Ted Cheng/Product Manager:

(Name / Position)

(Signatur

Taiwan

July 24th, 2015

(Place)

(Date)